

Versionen und technische Daten

			
Modellbezeichnung	EC-09N mit Gürtelhalter	EC-15W Pager-Uhr mit USB Kontakt Ladegerät	EC-16CP mit Gürtelhalter, Ladegerät
NEU 06/2024 EC-20W Pager Uhr mit Farb-Display 	<ul style="list-style-type: none"> • PLL or crystal, 433.92/869.5MHz, POCSAG • Alert mode: Sound, vibrate, LED, Silent. • 4 or 8 line English display, 3 zoom mode (English). • Language support: English, Germany, Korean, Turkey, Italy, French, etc. • Out of range, low battery, repeat message, unread message indicator. • Menu selectable, User choice special functions for themselves. • Second watch function • AAA 1.5V Alk. • Water resist, Easy charging 	<ul style="list-style-type: none"> • PLL or crystal, 433.92/869.5MHz, POCSAG Alert mode: Sound, vibrate, LED, Silent. • 4 or 8 line English display, 3 zoom mode (English). • Language support: English, Germany, Korean, Turkey, Italy, French, etc. • Out of range, low battery, repeat message, unread message indicator. • Menu selectable, User choice special functions for themselves. • Second watch function • Rechargeable Li battery • Water resist, Easy charging 	<ul style="list-style-type: none"> • PLL or crystal, 433.92/869.5MHz, POCSAG • Alert mode: Sound, vibrate, LED, Silent. • 4 or 8 line English display, 3 zoom mode (English). • Language support: English, Germany, Korean, Turkey, Italy, French, etc. • Out of range, low battery, repeat message, unread message indicator. • Menu selectable, User choice special functions for themselves. • Second watch function • Rechargeable Li battery • Water resist, Easy charging
Frequency Range	: 433.92/869.5MHz	: 433.92/869.5MHz	: 433.92/869.5MHz
Cap Codes	: 8	: 8	: 8
Baud Rate	: 512, 1200, 2400 bps	: 512, 1200, 2400 bps	: 512, 1200, 2400 bps
Paging Sensitivity	: -106DB @ 512 bps	: -106DB @ 512 bps	: -106DB @ 512 bps
	: -105DB @ 1200 bps	: -105DB @ 1200 bps	: -105DB @ 1200 bps
	: -104DB @ 2400 bps	: -104DB @ 2400 bps	: -104DB @ 2400 bps
Channel Spacing	: 25 KHz or 12.5 KHz	: 25 KHz or 12.5 KHz	: 25 KHz or 12.5 KHz
Frequency Deviation	: +/-4.5 KHz	: +/-4.5 KHz	: +/-4.5 KHz
Frequency Stability	: +/- 10PPM	: +/- 10PPM	: +/- 10PPM
Selectivity	: > 55dB	: > 55dB	: > 55dB
Image Rejection	: > 52dB	: > 52dB	: > 52dB
Spurious Rejection	: > 55dB	: > 55dB	: > 55dB
Intermediation	: > 50dB	: > 50dB	: > 50dB
Alert Tone Loudness	: 72dB+ @ 12 inch	: 72dB+ @ 12 inch	: 72dB+ @ 12 inch
Display	: 16 characters / line, 22 characters max	: 16 characters / line, 22 characters max	: 16 characters / line, 22 characters max
Memory Capacity	: up to 3000 characters	: up to 3000 characters	: up to 3000 characters
Messages	: 40 max	: 40 max	: 40 max
Weight	: 68 g with battery	: 65 g with battery	: 65 g with battery
Dimensions	: 75*53*18 mm	: 52*46*14 mm	: 85*53*11.5 mm
Battery Type	: 1x AAA 1.5V bzw. Li battery 600mAh	: Li battery 3.7V 300mAh	: Li battery, 3.7V 650mAh
Operating Temperature	: -10 to 50 C	: -10 to 50 C	: -10 to 50 C

** Technische Änderung vorbehalten