

KH08 SERIES

ARTICLE PROPERTIES

SENSOR TYPE	Inductive sensor	CONNECTION TYPES (<i>see table</i>)	
SIZE	∅ 8 mm	• cable	PVC, 0.34 mm ² , 2 m**
RATED OPERATING DISTANCE	<i>see table</i>		
NUMBER OF CONDUCTORS	2-wire / 3-wire (<i>see table</i>)		** other cable lengths are available on request

MECHANICAL DATA

MOUNTING	flush (<i>see table</i>)
HOUSING	cylindrical
MATERIAL HOUSING	stainless steel
MATERIAL SENSING SURFACE	PBT
TIGHTENING TORQUE LOCKING	—
STANDARD TEST	FE360
ATTENUATION COEFFICIENT	St37 = 1, V2A = 0.7, Al = 0.3

ELECTRICAL DATA

OPERATING VOLTAGE	DC: 10 ... 30 V DC
RATED OPERATING CURRENT	2-wire: ≤ 100 mA 3-wire: ≤ 200 mA
SWITCHING FREQUENCY	<i>see table</i>
SWITCHING OUTPUT	<i>see table</i>
FUNCTION INDICATOR	yellow LED
HYSTERESIS	3 ... 15 %
TEMPERATURE DRIFT	±10 %
SHORT-CIRCUIT PROTECTION	yes
OVERLOAD RESISTANCE	yes
REVERSE POLARITY PROTECTION	yes

ENVIRONMENTAL CONDITIONS

PROTECTION CLASS	IP67	VIBRATION RESISTANCE (EN 60068-2-27)	55 Hz, 1 mm
AMBIENT TEMPERATURE	-25 ... 70 °C	SHOCK RESISTANCE (EN 60068-2-6)	30g/11 ms

STANDARDS AND DIRECTIVES

LOW-VOLTAGE SWITCHGEAR AND CONTROLGEAR	DIN EN IEC 60947-5-2:2021-04
---	------------------------------

APPROVALS



KH08 SERIES

DC 2-WIRE OUTPUT CABLE


Article number	Mounting	Rated operating distance Sn	Switching output (wiring diagram)	Switching frequency	Dimensions
Fi2-KH08SS-OD6L	flush	2 mm	DC NO (WD1)	1000 Hz	see Fig. 1
Fi2-KH08SS-CD6L	flush	2 mm	DC NC (WD2)	1000 Hz	see Fig. 1

DC 3-WIRE OUTPUT CABLE

Article number	Mounting	Rated operating distance Sn	Switching output (wiring diagram)	Switching frequency	Dimensions
Fi2-KH08SS-OP6L	flush	2 mm	PNP NO (WD7)	1000 Hz	see Fig. 1
Fi2-KH08SS-ON6L	flush	2 mm	NPN NO (WD8)	1000 Hz	see Fig. 1
Fi2-KH08SS-CP6L	flush	2 mm	PNP NC (WD9)	1000 Hz	see Fig. 1
Fi2-KH08SS-CN6L	flush	2 mm	NPN NC (WD10)	1000 Hz	see Fig. 1


DIMENSIONS

Fig. 1 Inductive sensor with cable (flush)




WIRING DIAGRAMS


WD1 DC 2-wire NO




WD2 DC 2-wire NC




WD7 DC 3-wire PNP NO




WD8 DC 3-wire NPN NO



WD9 DC 3-wire PNP NC



WD10 DC 3-wire NPN NC



ELCO Industrie Automation GmbH
Benzstrasse 7
71720 Oberstenfeld
Deutschland
E-Mail: info@elco-automation.de



www.elco-automation.de

C+R Automations- GmbH

Nürberger Straße 45
90513 Zirndorf

Tel. +49 (0)911 656587-0
E-Mail: info@crautomation.de
www.crautomation.de